

Datenblatt / data sheet KKC 04 - MCS



Parameter	KKC 04-MCS
Schweißenergie max. <i>Welding Energy max.</i>	4,16 kW
Kondensatorkapazität max. <i>Capacitor capacitance max.</i>	4920 μ F (4100 + 820) μ F
Ladespannung max. <i>Maximum loading voltage</i>	1300 V (Niederspannung / <i>Low Voltage</i>)
Spitzenstrom max. <i>Maximum peak current</i>	60 kA
Einspeisung <i>Power supply</i>	3 x 350 ...480V 50/60 Hz Leistungselektronik – kein Ladetransformator erforderlich <i>Power electronics - no loading transformer required</i>
Absicherung <i>Main Fuse</i>	16 A
Elektrodenkraft max. <i>Maximum force</i>	8 kN
Elektrodenantrieb <i>Electrode drive</i>	servo-motorisch <i>servo-driven</i>
Ausladung max. <i>Maximum throat depth</i>	100 mm
Polplattenabstand max. <i>Distance of contact plates</i>	200 mm
Abmessungen (B x H x T) <i>Dimensions (W x H x D)</i>	1300 x 1800 x 1200 mm
Gewicht <i>Weight</i>	ca. 1100 kg



Beispielbild
Example picture

Technische Änderungen vorbehalten - Subject to technical changes